

Reolink-Go-PT-IP-Camera-Specifications		
	Model	Reolink Go PT
Video & Audio	Image Sensor	Starlight CMOS Image Sensor
	Video Resolution	1080p HD at 15 frames/sec
	Video Format	H.264
	Field of View	Fixed Lens, 105° Diagonal
	Pan/Tilt Angle	Horizontal: 355°
		Vertical: 140°
	Night Vision	Up to 10m (33 ft)
PIR Detection & Alerts	Digital Zoom	6x Digital Zoom
	Audio	Speaker and microphone for two-way audio
	PIR Detecting Distance	Adjustable, up to 10m (33ft)
	PIR Detecting Angle	90° Horizontal
	Audio Alert	Siren (customizable)
3G/4G Bandwidth	Other Alerts	Instant email alerts and push notifications
	Frequency Bands	Europe Version: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		America Version: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia Version: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL)
		LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL)
		HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL)
		UMTS: Max 384Kbps (DL), Max 384Kbps (UL)
Power	Battery	6000mAh rechargeable battery (battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel
	DC Power	5V/2A USB power adapter
Storage	Local Storage	Supports up to 128GB Micro SD card
	Cloud Storage	Supports Reolink Cloud (available in some countries)
Working Environment	Operating Temperature	-10°C to 55°C (14°F to 131°F)
	Weather Resistance	Weatherproof
Size & Weight	Size	Φ98 x 112mm (Φ3.7 x 4.4 in)
	Weight (Battery included)	485g (17.1 oz)
Warranty	Limited Warranty	2-Year Limited Warranty. For Support, Visit https://support.reolink.com/hc/en-us/