

Intercom building GSM panel lobby



Description

Open the Door By Auto-rejected Phone Calls By Authorized Numbers.
Up to 200 Authorized Phone Numbers, Special for Apartments.
User Friendly Design, No more Wiring Installation.
High Quantity Two-way Voice Communication.

Specifications

1. Quad-band 850/900/1800/1900Mhz.
2. FREE Charge. Open the Door By Auto-rejected Phone Calls By Authorized Numbers.
3. High Quality Two-way Voice Communication, and optional audio.
4. Every Family has a Admin Password and Authorize 5 Family Phone Numbers.
5. User Friendly Design, LED Screen, Alloy Shell , Easy for installation.
6. Up to 200 authorized phone numbers, Special for Apartments and Residential buildings.
7. Affordable Rates with Top Quality.
No More Wiring Installations
and other Complex Accessories.
8. 2 Relay Outputs (NC/NO), Well compatible with Electronic Locks and DVR Camera.
9. 12VDC Power Supply,
Relay Time Editable (1~300 seconds).
Default "0s", means not work.



Item	Reference Scope
DC Power supply	Standard adapter: DC 12V/1.5A
Power consumption	Standby:12V/70mA; Working Max.: 12V/300mA
GSM Frequency	850/900/1800/1900Mhz/ 3G WCDMA/3G CDMA2000
Transmit power	Class 4 (2W) at EGSM 900 and EGSM 850 Class 1 (1W) at GSM 1800 and GSM 1900
SIM interface	Supporting 3V SIM Card
External antenna	SMA Antenna interface, 50 Ohm
Max.Autorized Number	1000
Max. Room Number	200
Max. RFID Card	1000, non-contact RFID Card(M1 S50)
Relay Outputs	2, Rated: 5A/30VDC,5A/250VAC
Temperature range	-10 ~ +70 °C
Exterior dimension	273 × 130 × 50mm
Install Dimension	252 × 113 × 33mm
Wall-mount Dimension	252 × 113 × 33mm
Net Weight	1000 g

