


UTP CAT 6, 305 meters, Core diameter: 0.50mm, OFC, CM, red

Content of the Data Sheet																																																																							
Sheath Printing	TBD																																																																						
Customer No.		Customer Reference		White-Blue /Blue White-Orange /Orange Sheath Seperator Rip-cord White-Brown /Brown White-Green /Green 																																																																			
Category	SD U/UTP CAT6-4P-PVC																																																																						
Reference Standard	ISO/IEC11801、TIA-568-C.2																																																																						
Conductor	Material	SOLID-Bare Copper																																																																					
	Nom.O.D.(mm)	0.500	±0.005																																																																				
0.510																																																																							
Insulation	Material	HDPE																																																																					
	Diameter	0.88±0.05mm																																																																					
Sheath	Thickness	0.50±0.05 mm		FLUKE Permanent link Technical Performance (≤85m) : <table><tr><th>Frequency (MHz)</th><th>RL (dB)</th><th>ATT (dB)</th><th>NEXT (dB)</th><th>DELAY (ns)</th></tr><tr><td>1</td><td>19.1</td><td>3.0</td><td>65.0</td><td>570.0</td></tr><tr><td>4.0</td><td>21.0</td><td>3.5</td><td>64.1</td><td>552.0</td></tr><tr><td>8.0</td><td>21.0</td><td>5.0</td><td>59.4</td><td>546.7</td></tr><tr><td>10.0</td><td>21.0</td><td>5.5</td><td>57.8</td><td>545.4</td></tr><tr><td>16.0</td><td>20.0</td><td>7.0</td><td>54.6</td><td>543.0</td></tr><tr><td>20.0</td><td>19.5</td><td>7.9</td><td>53.1</td><td>542.1</td></tr><tr><td>25.0</td><td>19.0</td><td>8.9</td><td>51.5</td><td>541.2</td></tr><tr><td>31.25</td><td>18.5</td><td>10.0</td><td>50.0</td><td>540.4</td></tr><tr><td>62.5</td><td>16.0</td><td>14.4</td><td>45.1</td><td>538.6</td></tr><tr><td>100</td><td>14.0</td><td>18.6</td><td>41.8</td><td>537.6</td></tr><tr><td>200</td><td>11.0</td><td>27.4</td><td>36.9</td><td>536.5</td></tr><tr><td>250</td><td>10.0</td><td>31.1</td><td>35.3</td><td>536.3</td></tr></table>			Frequency (MHz)	RL (dB)	ATT (dB)	NEXT (dB)	DELAY (ns)	1	19.1	3.0	65.0	570.0	4.0	21.0	3.5	64.1	552.0	8.0	21.0	5.0	59.4	546.7	10.0	21.0	5.5	57.8	545.4	16.0	20.0	7.0	54.6	543.0	20.0	19.5	7.9	53.1	542.1	25.0	19.0	8.9	51.5	541.2	31.25	18.5	10.0	50.0	540.4	62.5	16.0	14.4	45.1	538.6	100	14.0	18.6	41.8	537.6	200	11.0	27.4	36.9	536.5	250	10.0	31.1	35.3	536.3
	Frequency (MHz)	RL (dB)	ATT (dB)				NEXT (dB)	DELAY (ns)																																																															
	1	19.1	3.0				65.0	570.0																																																															
	4.0	21.0	3.5				64.1	552.0																																																															
	8.0	21.0	5.0				59.4	546.7																																																															
10.0	21.0	5.5	57.8	545.4																																																																			
16.0	20.0	7.0	54.6	543.0																																																																			
20.0	19.5	7.9	53.1	542.1																																																																			
25.0	19.0	8.9	51.5	541.2																																																																			
31.25	18.5	10.0	50.0	540.4																																																																			
62.5	16.0	14.4	45.1	538.6																																																																			
100	14.0	18.6	41.8	537.6																																																																			
200	11.0	27.4	36.9	536.5																																																																			
250	10.0	31.1	35.3	536.3																																																																			
External O.D.	5.3±0.4 mm																																																																						
Surface	Clean, Frap, Satiation																																																																						
Material	PVC (complies RoHS)																																																																						
Color	TBD																																																																						
Surface Printing	Letter height	3.0±0.3mm																																																																					
	Color	Black																																																																					
	Print error & Space	≤±0.5%, 1m																																																																					
Core Color	1 White- Blue /Blue	2 White-Orange /Orange																																																																					
	3 White-Green /Green	4 White- Brown /Brown																																																																					
Packing	Wooden Tray & Carton																																																																						
Carton dimension	According to the requires																																																																						
Packing length	305±1.5m																																																																						
Rip-cord	Yes	Drain wire	No	<table><tr><th>Frequency (MHz)</th><th>PSNEXT (dB)</th><th>ELFEXT (dB)</th><th>PSELFEXT (dB)</th></tr><tr><td>1</td><td>62.0</td><td>64.2</td><td>61.2</td></tr><tr><td>4</td><td>61.8</td><td>52.1</td><td>49.1</td></tr><tr><td>8</td><td>57.0</td><td>46.1</td><td>43.1</td></tr><tr><td>10</td><td>55.5</td><td>44.2</td><td>41.2</td></tr><tr><td>16</td><td>52.2</td><td>40.1</td><td>37.1</td></tr><tr><td>20</td><td>50.7</td><td>38.2</td><td>35.2</td></tr><tr><td>25</td><td>49.1</td><td>36.2</td><td>33.2</td></tr><tr><td>31.25</td><td>47.5</td><td>34.3</td><td>31.3</td></tr><tr><td>62.5</td><td>42.7</td><td>28.3</td><td>25.3</td></tr><tr><td>100</td><td>39.3</td><td>24.2</td><td>21.2</td></tr><tr><td>200</td><td>34.3</td><td>18.2</td><td>15.2</td></tr><tr><td>250</td><td>32.7</td><td>16.2</td><td>13.2</td></tr></table>			Frequency (MHz)	PSNEXT (dB)	ELFEXT (dB)	PSELFEXT (dB)	1	62.0	64.2	61.2	4	61.8	52.1	49.1	8	57.0	46.1	43.1	10	55.5	44.2	41.2	16	52.2	40.1	37.1	20	50.7	38.2	35.2	25	49.1	36.2	33.2	31.25	47.5	34.3	31.3	62.5	42.7	28.3	25.3	100	39.3	24.2	21.2	200	34.3	18.2	15.2	250	32.7	16.2	13.2													
Frequency (MHz)	PSNEXT (dB)	ELFEXT (dB)	PSELFEXT (dB)																																																																				
1	62.0	64.2	61.2																																																																				
4	61.8	52.1	49.1																																																																				
8	57.0	46.1	43.1																																																																				
10	55.5	44.2	41.2																																																																				
16	52.2	40.1	37.1																																																																				
20	50.7	38.2	35.2																																																																				
25	49.1	36.2	33.2																																																																				
31.25	47.5	34.3	31.3																																																																				
62.5	42.7	28.3	25.3																																																																				
100	39.3	24.2	21.2																																																																				
200	34.3	18.2	15.2																																																																				
250	32.7	16.2	13.2																																																																				
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)		≥13.5																																																																				
	Elongation(%)		≥150																																																																				
	Aging Period (°C×hrs)		100°C×24h×7d																																																																				
	After Aging Tensile Strength(Mpa)		≥12.5																																																																				
	Elongation(%)		≥125																																																																				
Electrical Characteristics (20°C)	Cold bend(-20±2°C×4h) 8×Cable O.D., No visible cracks																																																																						
	1.0-250.0MHz Impedance ((Ω)	100±15																																																																					
	1.0-250.0MHz Delay Skew (ns/100m)	≤45																																																																					
	DC Resistance (Ω/100m) max	9.5																																																																					
	DC Conductor Resistance Unbalance (%)	max	5.0																																																																				