

Alarm system E3 kit host 2×PIR, 2×Remote, 1×door Sensor, 1×siren, 1×adapter, 1×sm



- 3 Wired Zone + 99 Wireless Zone
- Embedd CPU with 32-bit Cortex M3 Kernel
- Multi-task based OS Design with excellent user operating experience
- Two Way Audio (Voice Intercom)
- WI-FI/ GSM/ GPRS networking alarm system with multiple notification methods
- EOL R wired detecting zones
- Support add 90 Remote controllers/ WIRELESS DETECTORS, 10 RFID tags
- Zone Attributes: 8 types (24hours zone/ cheme zone/ Fire alarm zone/ Delay Zone/ Normal Zone etc.)
- Multi-groups timing-arm/disarm function.
- Wireless Transmission Frequency 433.92MHz
- Auto Dial: support 5group of phone numbers
- SMS Function: support SMS Alert(Arm/disarm status/Alarm status)
- Built in siren Sound Level: 80dB
- APP Supported (Android/IOS), Push for arm/disarm, alarm, device status
- Touch keypad, simplified Operation Interface
- Low Power Function: Yes
- Phone/ SMS/ APP message remotely control: arming, disarming, monitoring or announcement

Parameters

LCD Display	2.4" Colorful LCD Display
CPU	32Bites Cortex M3
Dial function	SUPPORT 5Group of telephone call
Power	Plug in power supply, micro USB 110/220VAC to 5V DC
Backup battery	3.7V 1000mAh Lithium Battery
Consumption	<150mA @normal
Siren Output	<300mA
Radio Frequency	315/433/868MHz(optional) Default 433MHz
RF Code	EV 1527
GSM Band	850/900/1800/1900MHz
WIFI	IEEE802.11b/g/n
APP	Tuya (IOS, Android)
Language	Multi languages: ENG/CN/RU/DE/SPANISH/TURKISH/ITALIAN,PORTUGUEESE

Standard Packing

Alarm Panel	× 1
Wireless PIR	× 1
Wireless Door Sensor	× 1
Remote Controller	× 2
RFID Card	× 2
Wired Siren	× 1
USB Adapter	× 1